

FP1800HBMAX 18" TFT Active Matrix LCD Monitor Specification

Grayscale 1.3MP
Medical Grade

LCD

Screen Size:	18.1" (460 mm) Diagonal
Display Area:	14.1" x 11.3" (386 x 287 mm)
Bit Depth:	8 bit grayscale
Viewing Angle:	80° Up, 80° Down, 80° Left, 80° Right
Brightness:	700 NITS (cd/m ²) 204 FT/L Maximum
Contrast Ratio:	400:1

Video Signals

Horizontal Frequency:	31 ~ 80 kHz
Vertical Frequency:	56 ~ 75 Hz

Connectors

Input:	Analog .714 Vp-p + 75 ohm (D-sub), Digital (DVI-D), S-Video
Sync Type:	Separate/Composite/Sync on Video
Signal Cable:	Analog 15 pin D-sub, DVI Cable, S-Video Cable

Resolution

1280 x 1024 Pixels (60-75 Hz), 1152 x 900,
1024 x 768 (60-75 Hz), 800 x 600, 640 x 480, NTSC/PAL

Features

User Controls:	Power, Brightness, Contrast Horizontal / Vertical Position Image Lock (Coarse / Fine) Grayscale Control / Grayscale Recall Source Select / OSD Position / Duration
Tilt-swivel Base:	Swivel, Tilt, Height, Pivot (Lock / Unlock) Portrait / Landscape Display Wall / Arm Mounting (VESA Standard)
Touch Panel Options:	Capacitive, Resistive, Surface Acoustic Wave

Physical

W x H x D (w/ stand):	20.8" x 20.3" x 11.0" (530 x 515 x 280 mm)
Weight :	15.2 lbs (6.9 Kg) Unpacked 15.9 lbs (7.2Kg) Packed

Environment

Operating:	10°– +40°C; 10%–80% RH (Non-condensing)
Storage:	-25°– +45°C; 5%–95% RH (Non-condensing)

Power

Management:	EPA Energy Star/Nutek
Consumption:	Typical : 50 Watts (On Mode)
Input:	100–240 VAC, 50/60 Hz

Agencies

cUL 2601-1, FCC, CE, VCCI, MIC

Limited Warranty

24 month Factory Return

**IMAGE SYSTEMS
CORPORATION**
6103 BLUE CIRCLE DRIVE
MINNETONKA, MN 55343
PHONE: (952) 935-1171
FAX: (952) 935-1386
www.imagesystemscorp.com



FP1800hbmax.doc 10/15/03 (Rev. D)
Features and specifications are subject to change without prior notice.
The Image Systems Logo is a registered trademark of Image Systems Corporation.
©03 Image Systems Corporation. All rights reserved.