
LCD

Screen Size:	24.0" (61.1 cm) Diagonal
Display Area:	20.4" x 12.75" (51.84 x 32.4 cm)
Pixel Pitch:	0.27 mm
Color Depth:	8 Bit (256) Gray Scale, 24 Bit (16.7 M) Color
Viewing Angle:	80° Up, 80° Down, 80° Left, 80° Right
Brightness:	240 NITS (cd/m ²) Maximum
Contrast Ratio:	400:1 Typical

Video Signals

Video Signal:	RGB Analog, 0.714 Vp-p, 75 Ω
Horizontal Frequency:	30–145 kHz, Auto-synchronous
Vertical Frequency:	56–85 Hz, Auto-synchronous

Connectors

Analog Input:	15-pin Mini D Sub Conn, Digital 8 bit DVI-D, S-Video/CVBS
---------------	---

Resolution

Maximum:	1920 Pixels (H) x 1200 Lines (V) / 60 Hz also VGA, SVGA, XGA, SXGA, UXGA
Aspect Ratio:	16:10, 5:4 and 4:3

Sync Type

Separate H&V, Composite Sync, Sync on Green,
S-Video, CVBS

Physical

W x H x D:	24.88"x 16.29"x 11.22" (63.2x 41.4x 28.5 cm)
Weight :	22 Lbs. (9.9 kg) without base
VESA Mounting Interface:	100 mm

Environment

Operating:	10°–40°C; 10%–80% RH (Non-condensing)
Storage:	-25°–45°C; 5%–95% RH (Non-condensing)

Power

Management:	EPA Energy Star/Nutek
Consumption:	80 W On mode, DPMS under 9 W
Input:	100–240 VAC, 50/60 Hz

Agencies

UL 1950, FCC, CE, TUV, TCO95

Limited Warranty

36 month Factory Return

IMAGE SYSTEMS
CORPORATION
6103 BLUE CIRCLE DRIVE
MINNETONKA, MN 55343
PHONE: (952) 935-1171
FAX: (952) 935-1386
www.imagesystemscorp.com

